

Performance	CSA 1300Z	CSA 2300Z
Rated Power into 4 Ω or 8 Ω ; 1kHz, $\leq$ 0.5% THD	300W	300W
Number of Output Channels	1	2
Insertion Loss (70V & 100V outputs)	1 dB maximum	
Input Sensitivity (8 Ω Load)	Balanced line input: 775mV _{RMS} ; RCA Mono Sum input: 300mV _{RMS}	
Frequency Response (8 Ω , 20Hz - 20kHz, tone ctrls set to flat response)	+/- 1.0 dB	
Total Harmonic Distortion (THD) (@ Full rated power, 20Hz-20kHz)	<0.5%	
Signal-to-Noise Ratio (Ref. rated output, 22KHz BW, A-weighted)	>97dB	
Input Impedance (nominal)	Euro Block: 20 k Ω (balanced); RCA: 10 k Ω	
Maximum Input Level	+22dBu (Nominal)	
Crosstalk (Ref. rated power, A-weighted, 1kHz)	<-70 dB	
Tone Controls (Bass and Treble non-detented potentiometers on each channel)	Bass +/-12dB @100Hz Treble +/-12dB @10kHz	
Nominal AC Line Voltages	100V, 120V, 220V, 230-240V, 50/60 Hz	
Minimum Load Impedance Low-Z Output 70V Output 100V Output	4 Ω 12 Ω 24 Ω	4 Ω 12 Ω 24 Ω
Operating Temperature/Humidity	0°C to 35°C @ 95% R.H. (non-condensing)	
Storage Temperature	-20°C to 85°C	
Dimensions & Weight		
Net Weight (preliminary estimate)	13.1 lb (5.95 kg)	17.8 lb (8.05 kg)
Dimensions	Width: 17.0 in. (432 mm) Depth: 10.8 in. (274 mm) Height: 3.5 in. (89 mm)	
Shipping Weight	16.4 lb (7.45 kg)	20.6 lb (9.35 kg)