



Confidea T-CD

Confidea Tabletop Chairman Discussion Unit



Description

The Confidea T-CD is Televic's tabletop chairman unit for basic discussion systems. It combines a slim, contemporary design and excellent intelligibility with effortless ease of use. The units are equipped with a microphone On/Off or request-to-speak button and have two headphone outputs with a single volume control. The chairman version has 2 additional buttons compared to the delegate unit: "Next-in-line" and "Priority". The units interconnect in daisy chain over Cat 5e Plixus® network cabling. The RJ45 connectors are hidden in the base of the unit and the cables are held in place by two notches in the unit housing.

Benefits

The Confidea T-CD is a *sleek and stylish solution* and can be set up in the blink of an eye. The input and output connections are *auto-sensing and interchangeable*. As a result, installation is *easy, fast, and straightforward*, making it the ideal system for frequently changing environments. The removable microphone is *immune for mobile phone interference*, so delegates can leave their phones switched on during the meeting. The Confidea T-CD is backed by the Plixus® network with redundant cabling and hot swapping options to ensure *maximum reliability*. Finally, its shielded microphone is immune to mobile phone interference.

Features

- Built-in high-quality loudspeaker which is automatically muted when the microphone is active, to prevent acoustic feedback
- Microphone On/Off or request-to-speak push button with two signaling LEDs
- Two headphone outputs with single volume control
- Next-in-line push button
- Priority push button
- Trademark natural Televic Sound

Connectivity

- Screw-lock socket to connect a removable microphone.

| | |
|------------------|-------------------|
| D-MIC30SL | 71.98.0053 |
| D-MIC40SL | 71.98.0054 |
| D-MIC50SL | 71.98.0055 |

- Two RJ 45 connectors for loop through cabling
- Two 3.5 mm stereo jack sockets for headphones
- Plixus-powered

Software

To fully configure, manage, and use the unit, Televic's CoCon management software is required. The following standard licenses are available:

| | |
|-------------------------|-------------------|
| CoCon Discussion | 71.98.1101 |
| CoCon Signage | 71.98.1102 |

Certifications

| Region | Certification |
|--------|---------------|
| Europe | CE |

Specifications

| Mechanical | |
|----------------------|----------------------------|
| Material | PC/ABS |
| Color | Black matt, RAL9011 |
| Size (mm) | 230 (w) × 130 (h) × 60 (d) |
| Size packed (mm) | 250 (w) × 150 (h) × 90 (d) |
| Weight (g) | 480 |
| Weight packed (g) | 620 |
| Electrical | |
| Voltage | 48 VDC |
| Consumption | 4 W |
| Speaker Output | |
| Maximum output power | > 1 W |
| Frequency response | 200-20,000 Hz |
| Dynamic range | > 90 dB |
| THD @ nominal level | < 0.1% |
| Load impedance | 8 Ω |
| Headphone Output | |
| Maximum output | > 10 mW |
| Frequency response | 22-22,000 Hz |
| Dynamic range | > 90 dB |
| THD @ nominal level | < 0.1% |
| Load impedance | 16-32 Ω |
| Microphone Input | |
| Nominal input level | -54.7 dBV |
| Maximum input level | -24.6 dBV |
| Input impedance | 1 kΩ |
| Dynamic range | > 93 dB |
| Frequency response | 25-20,000 Hz |
| THD @ nominal level | < 0.1% |

All information copyright **Televic Conference**, 2015. Version 1.0, October 2015

—
 Leo Bekaertlaan 1 · 8870 Izegem · Belgium
 Tel. +32 51 30 30 45
 Fax +32 51 31 06 70
 E-mail: conference@televic.com
 Web: <http://www.televic-conference.com>
Televic reserves the right to change this document without notice.